

Axpert V Off-Grid Inverter

Axpert VM 1000-12 /
Axpert VM 2000-24Axpert VP 1000-12 /
Axpert VP 2000-24Axpert VP3000-24 /
Axpert VM3000-24Axpert VM 3000-24 Plus /
Axpert VP 5000-48 /
Axpert VM 5000-48

- Pure sine wave solar inverter
- Output power factor 1
- Selectable high power charging current
- Wide DC input range
- Selectable input voltage range for home appliances and personal computers
- Configurable AC/Solar input priority via LCD setting
- Compatible to AC mains or generator power
- Auto restart while AC is recovering
- Overload and short circuit protection
- Smart battery charger design for optimized battery performance
- Cold start function
- Optional anti-dusk kit

Axpert V Off-Grid Inverter Selection Guide

MODEL	Axpert VP 1000-12	Axpert VM 1000-12	Axpert VP 2000-24	Axpert VM 2000-24	Axpert VP 3000-24	Axpert VM 3000-24	Axpert VM 3000-24 Plus	Axpert VP 5000-48	Axpert VM 5000-48	
Rated Power	1000VA/1000W		2000VA/2000W		3000VA / 3000W			5000VA / 5000W		
INPUT										
Voltage	230 VAC									
Selectable Voltage Range	170-280 VAC (For Personal Computers) ; 90-280 VAC (For Home Appliances)									
Frequency Range	50 Hz/60 Hz (Auto sensing)									
OUTPUT										
AC Voltage Regulation (Batt. Mode)	230VAC ± 5%									
Surge Power	2000VA		4000VA		6000VA		10000VA			
Efficiency (Peak)	90% – 93%									
Transfer Time	10 ms (For Personal Computers) ; 20 ms (For Home Appliances)									
Waveform	Pure sine wave									
BATTERY										
Battery Voltage	12 VDC		24 VDC				48 VDC			
Floating Charge Voltage	13.5 VDC		27 VDC				54 VDC			
Overcharge Protection	16 VDC		31 VDC		33 VDC			63 VDC		
SOLAR CHARGER & AC CHARGER										
Solar Charger type	PWM	MPPT	PWM	MPPT	PWM	MPPT		PWM	MPPT	
Maximum PV Array Open Circuit Voltage	55 VDC	102 VDC	80 VDC	102 VDC	80 VDC	102 VDC	145 VDC	105 VDC	145 VDC	
Maximum PV Array Power	600 W	500 W	1200 W	1000 W	1200 W	1000 W	1500 W	2400 W	3000 W	
MPP Range @ Operating Voltage	N/A	17 – 80 VDC	N/A	30 – 80 VDC	N/A	30–80 VDC	30–115 VDC	N/A	60 – 115 VDC	
Maximum Solar Charge Current	50 A	40 A	50 A	40 A	50 A	40 A	60 A	50 A	60 A	
Maximum AC Charge Current	20 A	20 A	20 A	25 A	25A	25A	60 A	60 A	60 A	
Maximum Charge Current	50 A	60 A	50 A	60 A	70 A	60 A	120 A	110 A	120 A	
PHYSICAL										
Dimension, D x W x H (mm)	88 x 225 x 320				100 x 285 x 334		100 x 300 x 440	100 x 300 x 440		
Net Weight (kgs)	4.4	4.4	5	5	6.3	6.5	9.5	8.5	9.7	
Communication Interface	USB/RS232									
ENVIRONMENT										
Humidity	5% to 95% Relative Humidity (Non-condensing)									
Operating Temperature	-10°C to 50°C									
Storage Temperature	-15°C to 60°C									

Product specifications are subject to change without further notice.