



# RA12-230 (12V230Ah)

RA12-230 is a general purpose battery with 10 years floating design life, meet with IEC, JIS .BS and Eurobat standard. With heavy duty grid, thickness plates, special additives, RA series battery have long and reliable standby service life. Our RA Series batteries keep high consistent for better performance in series usage.



## Specification

Cells Per Unit	6
Voltage Per Unit	12
Capacity	230Ah@10hr-rate to 1.75V per cell @25°C
Weight	Approx. 67 Kg
Max. Discharge Current	2300A (5 sec)
Internal Resistance	Approx. 4 mΩ
Operating Temperature Range	Discharge: -20°C~60°C Charge: 0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C±5°C
Float charging Voltage	13.6 to 13.8 VDC/unit Average at 25°C
Recommended Maximum Charging Current Limit	69A
Equalization and Cycle Service	14.6 to 14.8 VDC/unit Average at 25°C
Self Discharge	RITAR batteries can be stored for more than 6 months at 25°C. Self-discharge ratio less than 3% per month at 25°C. Please charge batteries before using.
Terminal	Terminal F12
Container Material	A.B.S. (UL94-HB), Flammability resistance of UL94-V1 can be available upon request.



MH28539




G4M20206-0910-E-16



ISO9001:2000 Certificate

## Dimensions

Unit: mm Dimension: 521(L)×269(W)×208(H)



## Constant Current Discharge Characteristics: A (25°C)


F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
9.60V	626.9	469.6	396.4	259.1	149.5	89.46	61.83	50.67	41.48	28.57	24.16	13.29
10.0V	608.8	446.8	388.3	254.8	148.8	88.78	61.59	50.44	41.23	28.34	23.92	13.04
10.2V	590.7	431.0	382.2	252.6	147.4	88.11	61.12	50.20	40.99	28.11	23.69	12.80
10.5V	530.4	397.7	363.9	246.3	146.1	87.44	60.88	49.74	40.50	27.87	23.46	12.56
10.8V	478.8	362.7	335.4	235.5	142.6	85.87	59.23	48.56	39.77	27.41	23.23	12.32
11.1V	408.8	324.2	300.9	220.6	135.5	82.06	56.62	46.22	38.06	26.25	22.53	11.60

## Constant Power Discharge Characteristics: W(25°C)


F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
9.60V	6484	5001	4360	2954	1728	1054	735.8	604.0	494.8	341.1	288.7	159.3
10.0V	6356	4848	4290	2918	1723	1049	736.0	603.3	493.6	339.5	286.9	156.5
10.2V	6284	4720	4242	2897	1710	1042	732.8	602.0	491.9	337.3	284.3	153.6
10.5V	5720	4395	4046	2830	1695	1035	730.0	596.3	486.0	334.5	281.5	150.7
10.8V	5210	4051	3740	2713	1663	1022	710.1	582.7	477.2	328.9	278.7	147.8
11.1V	4576	3663	3367	2548	1592	983.8	679.4	554.6	456.7	315.0	270.4	139.1

All mentioned values are average values.


### Effect of temperature on long term float life




### Storage characteristic



### Charge characteristic Curve for standby use



### Discharge characteristic Curve



### Capacity Factors With Different Temperature

Battery Type		-20°C	-10°C	0°C	5°C	10°C	20°C	25°C	30°C	40°C	45°C
GEL Battery	6V&12V	50%	70%	83%	85%	90%	98%	100%	102%	104%	105%
	2V	60%	75%	85%	88%	92%	99%	100%	103%	105%	106%
AGM Battery	6V&12V	46%	66%	76%	83%	90%	98%	100%	103%	107%	109%
	2V	55%	70%	80%	85%	92%	99%	100%	104%	108%	110%

### Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/cell	1.75V	1.70V	1.60V
Discharge Current (A)	(A) ≤ 0.2C	0.2C < (A) < 1.0C	(A) ≥ 1.0C

### Maintenance & Cautions

<b>Float Service:</b>
※ Every month, recommend inspection every battery voltage.
※ Every three months, recommend equalization charge for one time.
Equalization charge method:
Discharge: 100% rate capacity discharge.
Charge: Max. current 0.3CA, constant voltage 2.4-2.45V/Cell charge 24h.
※ Effect of temperature on float charge voltage: -3mV/°C/Cell.
※ Length of service life will be directly affected by the number of discharge cycles, depth of discharge, ambient temperature and charging voltage.

**Charge the batteries at least once every six months, if they are stored at 25°C.**

Charging Method:

Constant Voltage	-0.2Cx2h+2.4-2.45V/cellx24h, Max. Current 0.3CA
Constant Current	-0.2Cx2h+0.1CAx12h
Fast	-0.2Cx2h+0.3CAx4.0h